

Data Sheet

Distilling / Rotary Evaporators



RV 10 basic V

The newly developed product line from IKA® in ergonomic, compact design with innovative functions to improve operating results. Rotary evaporators with integrated heating bath HB 10 basic (3 litre) inc. space saving vertical glassware (1 litre).

- Heating bath with adjustable safety circuit, "stand alone" operation possible, pivoting safety hood as accessory
- Safe and simple operation through ergonomically shaped operator unit in the front area
- Motorised lift (stroke 140 mm) with "safety stop" function, if the power cuts out the evaporator piston is automatically lifted out of the heating bath.
- Adjustable end position recognition to protect the glass from breaking
- Speed range from 20 to 280 rpm
- Smooth start from 100 rpm
- Digital speed display
- Moves right and left in interval operation for the drying process
- Timer function for time lapse controls
- Water-oil heating bath with integrated carry handles with safe handling
- Heats up quickly because of optimised bath volumes
- Cooling surface 1,200 cm²
- Push-off mechanism to loosen tightly fitting pistons
- Suitable for DIN EN 12697-3 (Asphalt test for hot asphalt)

Accessories: HB 10.1 Shield, HB 10.2 Protective cover, RV 10.900 Glassware vertical, RV 10.1 Glassware vertical, RV 10.3 Vertical-intensive condenser with manifold, RV 10.30 Vertical-intensive condenser with manifold, coated, RV 10.4 Dry Ice Condenser, RV 10.40 Dry Ice Condenser, coated, RV 10.5 Vertical condenser with manifold and cut-off valve for reflux distillation, RV 10.50 Vertical condenser with manifold and cut-off valve for reflux distillation, coated, RV 10.6 Vertical-intensive condenser with manifold and cut-off valve for reflux distillation, RV 10.60 Vertical-intensive condenser with manifold and cut-off valve for reflux distillation, coated, RV 10.70 Vapor tube (NS 29/32), RV 10.73 Vapor tube (NS 24/40), RV 10.2007 Evaporation flask (NS 24/40, 50 ml), RV 10.80 Evaporation flask (NS 29/32, 50 ml), RV 10.81 Evaporation flask (NS 29/32, 100 ml), RV 10.2008 Evaporation flask (NS 24/40, 100 ml), RV 10.82 Evaporation flask (NS 29/32, 250 ml), RV 10.2009 Evaporation flask (NS 24/40, 250 ml), RV 10.83 Evaporation flask (NS 29/32, 500 ml), RV 10.2010 Evaporation flask (NS 24/40, 500 ml), RV 10.84 Evaporation flask (NS 29/32, 1.000 ml), RV 10.2011 Evaporation flask (NS 24/40, 1.000 ml), RV 10.85 Evaporation flask (NS 29/32, 2.000 ml), RV 10.85 Evaporation flask (NS 24/40, 2.000 ml), RV 10.86 Evaporation flask (NS 29/32, 3.000 ml), RV 10.86 Evaporation flask (NS 24/40, 3.000 ml), RV 10.2017 Powder flask (NS 24/40, 500 ml), RV 10.300 Powder flask (NS 29/32, 500 ml), RV 10.2018 Powder flask (NS 24/40, 1.000 ml), RV 10.301 Powder flask (NS 29/32, 1.000 ml), RV 10.2019 Powder flask (NS 24/40, 2.000 ml), RV 10.302 Powder flask (NS 29/32, 2.000 ml), RV 10.400

Technical Data

Type of cooling	vertical
Cooling surface [cm ²]	1200
Motor principle	DC
Speed range [rpm]	20 - 280
Reversible direction of rotation	yes
Lift	Motor
Stroke [mm]	140
Heating temperature range [°C]	room temp. - 180
Heat output [W]	1300
Heat control accuracy [±K]	5
Bath volume max. [l]	3
Vacuum controller integrated	no
Timer	yes
Dimensions (W x H x D) [mm]	500 x 430 x 410
Weight [kg]	19.6
Permissible ambient temperature [°C]	5 - 40
Permissible relative moisture [%]	80
Protection class according to DIN EN 60529	IP 20
RS 232 interface	no
Analog output	no
Voltage [V]	220 - 240 / 100 - 120
Frequency [Hz]	50/60
Power input [W]	1400
Ident. No.	8023901

Evaporation cylinder (NS 24/40, 500 ml), RV 10.400 Evaporation cylinder (NS 29/32, 500 ml),
RV 10.401 Evaporation cylinder (NS 24/40, 1.500 ml), RV 10.401 Evaporation cylinder (NS
29/32, 1.500 ml), RV 10.2025 Foam brake (NS 24/40), RV 10.500 Foam brake (NS 29/32),
RV 10.600 Distilling spider with 6 distilling sleeves (NS 29/32), RV 10.2029 Distilling spider
with 6 distilling sleeves (NS 24/40), RV 10.601 Distilling spider with 12 distilling sleeves (NS
29/32), RV 10.2030 Distilling spider with 12 distilling sleeves (NS 24/40), RV 10.602 Distilling
spider with 20 distilling sleeves (NS 29/32), RV 10.602 Distilling spider with 20 distilling
sleeves (NS 24/40), RV 10.2034 Distilling spider with 5 flasks 50 ml (NS 24/40), RV 10.606
Distilling spider with 5 flasks 50 ml (NS 29/32), RV 10.607 Distilling spider with 5 flasks 100
ml (NS 29/32), RV 10.2035 Distilling spider with 5 flasks 100 ml (NS 24/40), RV 10.100
Receiving flask (KS 35/20, 100 ml), RV 10.101 Receiving flask (KS 35/20, 250 ml), RV 10.102
Receiving flask (KS 35/20, 500 ml), RV 10.103 Receiving flask (KS 35/20, 1.000 ml), RV
10.104 Receiving flask (KS 35/20, 2.000 ml), RV 10.105 Receiving flask (KS 35/20, 3.000 ml),
RV 10.200 Receiving flask, coated (KS 35/20, 100 ml), RV 10.201 Receiving flask, coated
(KS 35/20, 250 ml), RV 10.202 Receiving flask, coated (KS 35/20, 500 ml), RV 10.203
Receiving flask, coated (KS 35/20, 1.000 ml), RV 10.204 Receiving flask, coated (KS 35/20,
2.000 ml), RV 10.205 Receiving flask, coated (KS 35/20, 3.000 ml), RV 10.3000 Extension
plate, RV 10.8001 Seal, labworldsoft®, RV 10.5003 Pressure control valve, VC 2 IKAVAC®
Vacuum controller, LVS 105 T-ef, KV 600 cooling water supply, UC006 Unichiller, H 11 Mains
cable Euro plug, H 11 Mains cable USA plug, H 11 Mains cable CH plug, H 11 Mains cable
UK plug