



Thermo Scientific Revco High-Performance Laboratory Refrigerators and Freezers

Laboratory

Blood Bank

Chromatography

Pharmacy

Plasma

Enzyme


your samples
our obsession

Thermo
SCIENTIFIC

Thermo Scientific™ Revco™ High-Performance Laboratory Refrigerators and Freezers

It's a cold hard fact:

Temperature variation can have an impact on the viability of samples and the efficacy of reagents. These variations can shorten product shelf life, degrade enzymes and reduce vaccine effectiveness. Therefore, it's important to choose a high-performance refrigerator or freezer that has been designed for the demanding standards of your laboratory.



Our Revco high-performance lab refrigerators and freezers are designed from the ground up for your most demanding applications, with features not found in domestic units, including:

Advanced microprocessor-controlled setpoints for precise temperature regulation

Directional airflow for uniform temperature at all shelf levels

Key-operated alarms and setpoint security

Easy-to-read digital displays

Multi-pane, glass doors

Optional temperature recording charts to confirm storage parameters

Standard 1-inch access ports

We continually search for ways to enhance our products and processes responsibly:

- Reduce the use of refrigerants in our cold storage equipment
- Use solvent-free, paint technology
- We recycle scrap metal, copper and aluminum in our production facilities
- Fluorescent lighting in our refrigerators replaced with mercury-free, LED lights

TABLE OF CONTENTS

REFRIGERATORS



Laboratory
PAGE 8-9



Chromatography
PAGE 10-11



Blood Bank
PAGE 12-13




Pharmacy
PAGE 14-15


FREEZERS



Laboratory
PAGE 16-17



Plasma
PAGE 18-19



Enzyme
PAGE 20



**Services, Accessories
and Related Products**
PAGES 22-27

Advanced design. Quality construction.

Sample protection that fits your application.

Like a vault protecting your valuables, protection starts with a solid foundation:

- Powerful industrial compressors provide fast recovery from door openings and the addition of new samples
- Heavy walled, CFC-free insulation ensure temperature stability and minimize energy use
- Microprocessor control provides flexibility in setpoints and alarms, plus accurate temperature control

Our high-performance refrigerators and freezers are designed to meet UL and CE criteria for safety and performance. See ordering charts for certifications per specific voltages.




45.8 cu. ft. sliding door, chromatography refrigerator

Clockwise from L to R: 4.9 cu. ft. undercounter lab freezer,
29.2 cu. ft. blood bank refrigerator, 51.1 cu. ft. lab refrigerator,
23.3 cu. ft. enzyme freezer

SELECTOR GUIDE	4°C	-20°C	-30°C
Feature Selections			
UL/CE compliant	•	•	•
Keyed door security	•	•	•
Adjustable setpoint/alarm	•	•	•
Remote alarm contact	•	•	•
Electronic alarm/probe test	•	•	•
Available chart recorder	•	•	•
Standard access ports	•	•	•
Choice of shelves/drawers	•	•	•
Self-closing 90° stop door	•	•	•
Door type	solid or glass	solid	solid
Forced air cooling	•		•
Automatic defrost	•		•
Convection cooling		•	
Manual defrost		•	
Interior lighting	•		
Applications			
General storage	•	•	•
Reagents and kits	•		
Whole blood	•		
Plasma			•
Enzymes and temperature sensitive materials		•	
Chromatography apparatus and instrumentation	•		
Test samples	•	•	•
Biologicals	•	•	•
Culture media	•		
Patient medication	•	•	
Vaccines	•	•	•
Shelf life testing	•		
PCR reagents and primers	•	•	

Microprocessor-Based Controller

simplifies operation, improves reliability





Bright, Easy-to-Read Display

Lets you know at-a-glance if your unit is running within range. Visual and audio alarms are designed to alert you in the event of a problem. Immediate access to high and low temperature parameters with the press of a button.

Touchpad Scan

Changes main display; also used to access various programming and service functions (alarm mute, recall 6 minutes).








Digital Display

Indicates cabinet temperature during normal operation, flashes during alarm condition or setpoint adjustment. Displays other values with touchpad sequence.

Service Parameters

Touchpad sequence allows override access to control function defaults for troubleshooting functions.

Automatic and Manual Defrost Selection Guide

							
Cu. Ft. (L)	4.7 (133)	11.5 (326)	23.3 (659)	29.2 (826)	45.8 (1297)	51.1 (1447)	78.8 (2231)
Automatic Defrost Models							
Chromatography Refrigerators			•	•	•	•	•
High-Performance Lab Refrigerators	•	•	•	•	•	•	•
Blood Bank Refrigerators	•	•	•	•		•	
Pharmacy Refrigerators		•	•	•		•	
High-Performance Lab Freezers, -30°C	•	•	•	•		•	
Plasma Freezers, -30°C	•	•	•	•		•	
Manual Defrost Models							
Enzyme Freezer, -20°C			•	•			
High-Performance Lab Freezers, -20°C			•	•			

Remote alarm contacts are included on all models.

Laboratory Refrigerators

Our Revco **high-performance, laboratory refrigerators** are available in a wide range of cabinet sizes to fit virtually any application need. Each refrigerator combines advanced microprocessor temperature control with the highest quality cabinet construction and alarm systems. Positive-forced air circulation maintains temperature uniformity to protect your valuable samples and inventory.

- Forced air circulation for uniform temperature and fast door opening recovery
- Heat-free defrost for maximum uniformity
- Choice of glass or solid doors
- Four casters, front two are lockable
- 1" (2.5cm) insulated access port
- Bright, LED interior lighting
- Adjustable, epoxy-coated wire shelves are standard (optional drawers)
- TempTest electronic probe/alarm test
- Keyed on/off switch with setpoint security
- Self-closing door with 90° stop (except REL4504 model)
- Built-in remote alarm contacts
- Optional 4-20 milliamp output
- **NEW!** Optional +5°C setpoint can be customized for users validating lab refrigerators in the +2 to +8°C setpoint (not available on 45 cu. ft. sliding door or 78 cu. ft. trip door models; order option 7508TA with your lab refrigerator)

Thermo Scientific Revco High-Performance Laboratory Refrigerators With Glass Doors

Temperature Range: +1°C to +8°C, factory preset to +4°C (auto defrost) Optional +5°C setpoint available (order option 7508TA)

Model No.	Cu. Ft. (L)	Voltage (Hz)	Certification	Amps/ Breaker (Plug)	Cabinet	Door	Adjustable Shelves	Int. Dimensions* H x D x W inches (mm)	Ext. Dimensions* H x D x W inches (mm)	Ship Weight lb (kg)
RGL404A RGL404D RGL404V RGL404W	4.9 (133)	115 (60) 208/230 (60) 230 (50) 230 (50)	UL UL CE CE	8.0/15 (P1) 6.0/15 (P4) 6.0/15 (P7) 6.0/15 (P8)	undercounter	single	3	20.0 x 20.5 x 20.0 (508 x 521 x 508)	33.4 x 26.0 x 24.0 (850 x 660 x 610)	220 (100)
Exterior height before caster installation.										
RGL1204A RGL1204D RGL1204V RGL1204W	11.5 (326)	115 (60) 208/230 (60) 230 (50) 230 (50)	UL UL CE CE	9.4/15 (P1) 6.0/15 (P4) 6.0/15 (P7) 6.0/15 (P8)	space saver	single	4	52.4 x 21.75 x 20.0 (1331 x 553 x 508)	73.6 x 29.4 x 24.0 (1869 x 748 x 610)	280 (127)
RGL2304A RGL2304D RGL2304V RGL2304W	23.3 (659)	115 (60) 208/230 (60) 230 (50) 230 (50)	UL UL CE CE	9.4/15 (P1) 6.0/15 (P4) 6.0/15 (P7) 6.0/15 (P8)	upright	single	4	58.0 x 29.0 x 24.0 (1473 x 737 x 610)	79.2 x 37.2 x 28.0 (2012 x 945 x 711)	370 (168)
RGL3004A RGL3004D RGL3004V RGL3004W	29.2 (826)	115 (60) 208/230 (60) 230 (50) 230 (50)	UL UL CE CE	9.4/15 (P1) 6.0/15 (P4) 6.0/15 (P7) 6.0/15 (P8)	upright	single	4	58.0 x 29.0 x 30.0 (1473 x 737 x 762)	79.2 x 37.2 x 34.0 (2012 x 945 x 864)	435 (197)
REL4504A REL4504D REL4504V REL4504W	45.8 (1297)	115 (60) 208/230 (60) 230 (50) 230 (50)	UL UL CE CE	15.0/20 (P2) 8.5/15 (P4) 8.5/15 (P7) 8.5/15 (P8)	upright	double sliding	8	58.0 x 26.0 x 52.5 (1473 x 660 x 1334)	79.1 x 34.5 x 56.5 (2010 x 876 x 1435)	670 (304)
RGL5004A RGL5004D RGL5004V RGL5004W	51.1 (1447)	115 (60) 208/230 (60) 230 (50) 230 (50)	UL UL CE CE	15.0/20 (P2) 8.5/15 (P4) 8.5/15 (P7) 8.5/15 (P8)	upright	double	8	58.0 x 29.0 x 52.5 (1473 x 737 x 1334)	79.2 x 37.2 x 56.5 (2012 x 945 x 1435)	585 (265)
RGL7504A RGL7504D RGL7504V RGL7504W	78.8 (2231)	115 (60) 208/230 (60) 230 (50) 230 (50)	UL UL CE CE	16.0/20 (P2) 10.5/15 (P4) 10.5/15 (P7) 10.5/15 (P8)	upright	triple	12	58.0 x 29.0 x 81.0 (1473 x 737 x 2057)	79.2 x 37.2 x 85.0 (2012 x 945 x 2159)	805 (365)

* Published interior volumes are nominal; useable cu.ft. (L) capacities may be offset by shelves, drawers, blower coils, or cabinet protrusions. For specific cabinet dimensions and allowances, or for verification of clearance tolerances, contact our sales representative. Product performance may be affected by ambient temperature conditions, humidity conditions, sample loading preferences, and frequency of door openings. Contact our sales representative for specific inquiries regarding your application. 4.7 cu. ft. exterior dimensions are without casters.



Optional, inkless, seven day, graphic, chart recorder

Control Panel:

Keyed on/off switch with set point security

Microprocessor control system with audio and visual alarms

Bright, digital temperature display

Doors:

Spring-loaded, self closing doors with 90° stay-open feature

Lockable doors for added sample security

Cabinets shown: 23.3 cu. ft. single door (RGL2304) lab refrigerator with glass door and 51.1 cu. ft. double door (RGL5004) lab refrigerator with solid doors

Thermo Scientific Revco Laboratory Refrigerators With Solid Doors

Temperature Range: +1°C to +8°C, factory preset to +4°C (auto defrost) Optional +5°C setpoint available (order option 7508TA)

Model No.	Cu. Ft. (L)	Voltage (Hz)	Certification	Amps/ Breaker (Plug)	Cabinet	Door	Adjustable Shelves	Int. Dimensions* H x D x W inches (mm)	Ext. Dimensions* H x D x W inches (mm)	Ship Weight lb (kg)
REL404A	4.9	115 (60)	UL	8.0/15 (P1)	undercounter	single	3	20.0 x 20.5 x 20.0	33.4 x 26.0 x 24.0	220
REL404D	(133)	208/230 (60)	UL	6.0/15 (P4)				(508 x 521 x 508)	(850 x 660 x 610)	(100)
REL404V		230 (50)	CE	6.0/15 (P7)						
REL404W		230 (50)	CE	6.0/15 (P8)						
Exterior height before caster installation.										
REL1204A	11.5	115 (60)	UL	9.4/15 (P1)	space	single	4	52.4 x 21.75 x 20.0	73.6 x 29.4 x 24.0	280
REL1204D	(326)	208/230 (60)	UL	6.0/15 (P4)	saver			(1331 x 553 x 508)	(1869 x 748 x 610)	(127)
REL1204V		230 (50)	CE	6.0/15 (P7)						
REL1204W		230 (50)	CE	6.0/15 (P8)						
REL2304A	23.3	115 (60)	UL	9.4/15 (P1)	upright	single	4	58.0 x 29.0 x 24.0	79.2 x 37.2 x 28.0	370
REL2304D	(659)	208/230 (60)	UL	6.0/15 (P4)				(1473 x 737 x 610)	(2012 x 945 x 711)	(168)
REL2304V		230 (50)	CE	6.0/15 (P7)						
REL2304W		230 (50)	CE	6.0/15 (P8)						
REL3004A	29.2	115 (60)	UL	9.4/15 (P1)	upright	single	4	58.0 x 29.0 x 30.0	79.2 x 37.2 x 34.0	435
REL3004D	(826)	208/230 (60)	UL	6.0/15 (P4)				(1473 x 737 x 762)	(2012 x 945 x 864)	(197)
REL3004V		230 (50)	CE	6.0/15 (P7)						
REL3004W		230 (50)	CE	6.0/15 (P8)						
REL5004A	51.1	115 (60)	UL	15.0/20 (P2)	upright	double	8	58.0 x 29.0 x 52.5	79.2 x 37.2 x 56.5	585
REL5004D	(1447)	208/230 (60)	UL	8.5/15 (P4)				(1473 x 737 x 1334)	(2012 x 945 x 1435)	(265)
REL5004V		230 (50)	CE	8.5/15 (P7)						
REL5004W		230 (50)	CE	8.5/15 (P8)						
REL7504A	78.8	115 (60)	UL	16.0/20 (P2)	upright	triple	12	58.0 x 29.0 x 81.0	79.2 x 37.2 x 85.0	805
REL7504D	(2231)	208/230 (60)	UL	10.5/15 (P4)				(1473 x 737 x 2057)	(2012 x 945 x 2159)	(365)
REL7504V		230 (50)	CE	10.5/15 (P7)						
REL7504W		230 (50)	CE	10.5/15 (P8)						

* Published interior volumes are nominal; useable cu.ft. (L) capacities may be offset by shelves, drawers, blower coils, or cabinet protrusions. For specific cabinet dimensions and allowances, or for verification of clearance tolerances, contact our sales representative. Product performance may be affected by ambient temperature conditions, humidity conditions, sample loading preferences, and frequency of door openings. Contact our sales representative for specific inquiries regarding your application. 4.7 cu. ft. exterior dimensions are without casters.

► See pages 22-24 for Options and Accessories

Chromatography Refrigerators

Our **Revco high-performance chromatography refrigerators** are designed for a variety of applications requiring close temperature control, full access to chromatography instrumentation, and easy set-up of instrumentation and apparatus within the chamber.

- Forced air circulation for uniform temperature and fast door opening recovery
- Heat-free defrost for maximum uniformity
- Two 2" (5 cm) access ports with insulated hinged covers
- Duplex interior plug
- Four casters, front two are lockable
- Bright, LED interior lighting
- Adjustable, epoxy-coated wire shelves are standard (optional drawers)
- TempTest electronic probe/alarm test
- Keyed on/off switch with setpoint security
- Self-closing door with 90° stop (except REC4504 model)
- Built-in remote alarm contacts
- Optional 4-20 milliamp output



Thermo Scientific Revco High-Performance Chromatography Refrigerators

Temperature Range: +1°C to +8°C, factory preset to +4°C (auto defrost)

Model No.	Cu. Ft. (L)	Voltage (Hz)	Certification	Amps/ Breaker (Plug)	Door	Full Adjustable Shelves	Half Adjustable Shelves	Int. Dimensions* H x D x W inches (mm)	Ext. Dimensions* H x D x W inches (mm)	Ship Weight lb (kg)
REC2304A REC2304D REC2304V REC2304W	23.3 (659)	115 (60) 208/230 (60) 230 (50) 230 (50)	UL UL CE CE	9.4/15 (P1) 6.0/15 (P4) 6.0/15 (P7) 6.0/15 (P8)	single, glass	0	2	58.0 x 29.0 x 24.0 (1473 x 737 x 610)	79.2 x 36.4 x 28.0 (2012 x 925 x 711)	425 (193)
REC3004A REC3004D REC3004V REC3004W	29.2 (826)	115 (60) 208/230 (60) 230 (50) 230 (50)	UL UL CE CE	9.4/15 (P1) 6.0/15 (P4) 6.0/15 (P7) 6.0/15 (P8)	single, glass	0	2	58.0 x 29.0 x 30.0 (1473 x 737 x 762)	79.2 x 36.4 x 34.0 (2012 x 925 x 864)	435 (197)
REC4504A REC4504D REC4504V REC4504W	45.8 (1297)	115 (60) 208/230 (60) 230 (50) 230 (50)	UL UL CE CE	15.0/20 (P2) 8.5/15 (P4) 8.5/15 (P7) 8.5/15 (P8)	double, sliding glass	4	2	58.0 x 26.0 x 52.5 (1473 x 660 x 1334)	79.1 x 34.5 x 56.5 (2010 x 838 x 1435)	670 (304)
REC5004A REC5004D REC5004V REC5004W	51.1 (1447)	115 (60) 208/230 (60) 230 (50) 230 (W)	UL UL CE CE	15.0/20 (P2) 8.5/15 (P4) 8.5/15 (P7) 8.5/15 (P8)	double, glass	4	2	58.0 x 29.0 x 52.5 (1473 x 737 x 1334)	79.2 x 36.4 x 56.5 (2012 x 925 x 1435)	580 (263)
REC7504A REC7504D REC7504V REC7504W	78.8 (2231)	115 (60) 208/230 (60) 230 (50) 230 (W)	UL UL CE CE	16.0/20 (P2) 10.5/15 (P4) 10.5/15 (P7) 10.5/15 (P8)	triple, glass	8	2	58.0 x 29.0 x 81.0 (1473 x 737 x 2057)	79.2 x 36.4 x 85.0 (2012 x 925 x 2159)	965 (438)

* Published interior volumes are nominal; useable cu.ft. (L) capacities may be offset by shelves, drawers, blower coils, or cabinet protrusions. For specific cabinet dimensions and allowances, or for verification of clearance tolerances, contact our sales representative. Product performance may be affected by ambient temperature conditions, humidity conditions, sample loading preferences, and frequency of door openings. Contact our sales representative for specific inquiries regarding your application.



Optional inkless, seven day, graphic, chart recorder

Control Panel:

Keyed on/off switch with set point security

Microprocessor control system with audio and visual alarms

Bright, digital temperature display

Bright, LED interior lighting illuminates the entire cabinet

Epoxy-coated, wire open shelves, adjustable in 1 in. increments for flexibility, available in both full and half shelf

Doors:

Robust, spring-loaded, self closing doors with 90° stay-open feature (sliding glass on 45 cu. ft. model)

Safety glass, double-pane doors

Lockable doors for added sample security



Cabinets shown: 78.8 cu. ft. triple-door (REC7504) and 45.8 cu. ft. sliding door (REC4504) chromatography refrigerators



Blood Bank Refrigerators

Our **Revco high-performance blood bank refrigerators** are designed to meet strict requirements established by the AABB and FDA for storage of whole blood and blood components. DIN 58371 compliant for our 326, 659 and 826 liter capacity units (230V/50Hz only).

The complete selection of +4°C refrigerators feature simplified push-button alarm test functions and reliable, field-proven refrigeration systems.

- Forced air circulation for uniform temperature and fast door opening recovery
- Heat-free defrost for maximum uniformity
- Standard, stainless steel interior
- Built-in chart recorder (freestanding on 4.9 cu. ft. undercounter model)
- Second cabinet temperature probe
- Four casters, front two are lockable
- 1" (2.5cm) insulated access port
- Bright, LED interior lighting
- Stainless steel, full extendable and adjustable drawers (optional shelves)
- TempTest electronic probe/alarm test
- Keyed on/off switch with setpoint security
- Self-closing door with 90° stop
- Built-in remote alarm contacts
- Optional 4-20 milliamp output

Thermo Scientific Revco High-Performance Blood Bank Refrigerators

Temperature Range: +1°C to +8°C, factory preset to +4°C (auto defrost)

Model No.	Cu. Ft./L (Blood Bag Capacity)**	Voltage (Hz)	Certification	Amps/ Breaker (Plug)	Cabinet	Door	Drawers	Int. Dimensions* H x D x W inches (mm)	Ext. Dimensions* H x D x W inches (mm)	Ship Weight lb (kg)
REB404A REB404D REB404V REB404W	4.9/133 (64)	115 (60) 208/230 (60) 230 (50) 230 (50)	UL UL CE CE	8.0/15 (P1) 6.0/15 (P4) 6.0/15 (P7) 6.0/15 (P8)	undercounter	single, solid	2	20.0 x 20.5 x 20.0 (508 x 520 x 508)	33.4 x 26.0 x 24.0 (850 x 660 x 610)	220 (100)
An additional 2" is added when standard casters are installed.										
REB1204A REB1204D REB1204V REB1204W	11.5/326 (192)	115 (60) 208/230 (60) 230 (50) 230 (50)	UL UL CE CE	9.4/15 (P1) 6.0/15 (P4) 6.0/15 (P7) 6.0/15 (P8)	space saver	single, glass	6	52.4 x 21.75 x 20.0 (1331 x 552 x 508)	73.6 x 29.4 x 24.0 (1869 x 762 x 610)	320 (145)
REB2304A REB2304D REB2304V REB2304W	23.3/659 (385)	115 (60) 208/230 (60) 230 (50) 230 (50)	UL UL CE CE	9.4/15 (P1) 6.0/15 (P4) 6.0/15 (P7) 6.0/15 (P8)	upright	single, glass	7	58.0 x 29.0 x 24.0 (1473 x 737 x 610)	79.2 x 36.4 x 28.0 (2012 x 925 x 711)	470 (213)
REB3004A REB3004D REB3004V REB3004W	29.2/826 (426)	115 (60) 208/230 (60) 230 (50) 230 (50)	UL UL CE CE	9.4/15 (P1) 6.0/15 (P4) 6.0/15 (P7) 6.0/15 (P8)	upright	single, glass	6	58.0 x 29.0 x 30.0 (1473 x 737 x 762)	79.2 x 36.4 x 34.0 (2012 x 925 x 864)	505 (229)
REB5004A REB5004D REB5004V REB5004W	51.1/1447 (770)	115 (60) 208/230 (60) 230 (50) 230 (50)	UL UL CE CE	15.0/20 (P2) 8.5/15 (P4) 8.5/15 (P7) 8.5/15 (P8)	upright	double, glass	14	58.0 x 29.0 x 52.5 (1473 x 737 x 1334)	79.2 x 36.4 x 56.5 (2012 x 925 x 1435)	640 (290)

* Published interior volumes are nominal; useable cu. ft. (L) capacities may be offset by shelves, drawers, blower coils, or cabinet protrusions. For specific cabinet dimensions and allowances, or for verification of clearance tolerances, contact our sales representative. Product performance may be affected by ambient temperature conditions, humidity conditions, sample loading preferences, and frequency of door openings. Contact our sales representative for specific inquiries regarding your application. 4.9 cu. ft. exterior dimensions are without casters.

** Nominal capacity based on 450 mL whole blood bags.

Independent automated monitoring is required such as a chart recorder. Note: this medical application is considered Class II for FDA but is currently Class I for MDD.

Blood Bank Refrigerators



Standard, built-in, inkless, seven day, graphic, chart recorder (freestanding on undercounter model)

Control Panel:

Keyed on/off switch with set point security

Microprocessor control system with audio and visual alarms

Bright, digital temperature display

Bright, LED interior lighting illuminates the entire cabinet


Doors:

Spring-loaded, self closing doors with 90° stay-open feature

Lockable doors for added sample security

Safety glass, double-pane doors

Full extension, adjustable stainless steel drawers



Cabinets shown: 51.1 cu. ft. double door (REB5004) and 11.5 cu. ft. single door (REB1204) blood bank refrigerators

► See pages 22-24 for
Options and Accessories



Pharmacy Refrigerators

Available in four sizes, **our Revco high-performance pharmacy refrigerators** deliver stable temperature control over a range of +1°C to +8°C. They can be configured easily for accurate storage and retrieval of pharmacy products, and feature full extension stainless steel roll-out drawers.

- Forced air circulation for uniform temperature and fast door opening recovery
- Heat-free defrost for maximum uniformity
- Four casters, front two are lockable
- 1" (2.5cm) insulated access port
- Bright, LED interior lighting
- Stainless steel, full extendable and adjustable drawers
- TempTest electronic probe/alarm test
- Keyed on/off switch with setpoint security
- Self-closing door with 90° stop
- Built-in remote alarm contacts
- Optional 4-20 milliamp output
- Optional shelves

Thermo Scientific Revco High-Performance Pharmacy Refrigerators

Temperature Range: +1°C to +8°C, factory preset to +4°C (auto defrost)

Model No.	Cu. Ft. (L)	Voltage (Hz)	Certification	Amps/ Breaker (Plug)	Cabinet	Door	Drawers	Int. Dimensions* H x D x W inches (mm)	Ext. Dimensions* H x D x W inches (mm)	Ship Weight lb (kg)
RPR1204A RPR1204D RPR1204V RPR1204W	11.5 (326)	115 (60) 208/230 (60) 230 (50) 230 (50)	UL UL CE CE	9.4/15 (P1) 6.0/15 (P4) 6.0/15 (P7) 6.0/15 (P8)	upright	single, glass	5	52.4 x 21.8 x 20.0 (1320 x 552 x 500)	73.6 x 29.4 x 24.0 (1869 x 762 x 610)	320 (145)
RPR2304A RPR2304D RPR2304V RPR2304W	23.3 (659)	115 (60) 208/230 (60) 230 (50) 230 (50)	UL UL CE CE	9.4/15 (P1) 6.0/15 (P4) 6.0/15 (P7) 6.0/15 (P8)	upright	single, glass	6	58.0 x 29.0 x 24.0 (1473 x 737 x 610)	79.2 x 36.4 x 28.0 (2012 x 925 x 711)	470 (213)
RPR3004A RPR3004D RPR3004V RPR3004W	29.2 (826)	115 (60) 208/230 (60) 230 (50) 230 (50)	UL UL CE CE	9.4/15 (P1) 6.0/15 (P4) 6.0/15 (P7) 6.0/15 (P8)	upright	single, glass	6	58.0 x 29.0 x 30.0 (1473 x 737 x 762)	79.2 x 36.4 x 34.0 (2012 x 925 x 864)	505 (227)
RPR5004A RPR5004D RPR5004V RPR5004W	51.1 (1447)	115 (60) 208/230 (60) 230 (50) 230 (50)	UL UL CE CE	15.0/20 (P2) 8.5/15 (P4) 8.5/15 (P7) 8.5/15 (P8)	upright	double, glass	12	58.0 x 29.0 x 52.5 (1473 x 737 x 1334)	79.2 x 36.4 x 56.5 (2012 x 925 x 1435)	640 (290)

* Published interior volumes are nominal; useable cu.ft. (L) capacities may be offset by shelves, drawers, blower coils, or cabinet protrusions. For specific cabinet dimensions and allowances, or for verification of clearance tolerances, contact our sales representative. Product performance may be affected by ambient temperature conditions, humidity conditions, sample loading preferences, and frequency of door openings. Contact our sales representative for specific inquiries regarding your application.



Cabinets shown: and 11.5 cu. ft. single door (RPR1204) and 51.1 cu. ft. double door (RPR5004) pharmacy refrigerators

Bright, LED interior lighting illuminates the entire cabinet

Adjustable, full extension, stainless steel drawers



Optional, inkless, seven day, graphic, chart recorder

Control Panel:

Keyed on/off switch with set point security
Microprocessor control system with audio and visual alarms


Bright, digital temperature display

Doors:

Spring-loaded, self closing doors with 90° stay-open feature

Lockable doors for added sample security

Safety glass, double-panel doors



Automatic and Manual Defrost Laboratory Freezers

Our **Revco high-performance, laboratory freezers** are designed for medical and scientific applications requiring storage of reagents, pharmaceuticals, biologicals, and other commonly used laboratory materials such as primers, siRNA molecules and FBS. A range of models offers cabinet sizes to fit your specific space needs and storage volume requirements, from undercounter units to full size models. Available in both automatic and manual defrost options (manual defrost only available on 23.3 cu. ft./659L and 29.2 cu. ft. (826L.)

Automatic Defrost Models:

- Forced air circulation for uniform temperature and fast door opening recovery
- Non-invasive defrost with time and temperature guided cycle

Manual Defrost Models:

- Cold wall convection cooling for temperature uniformity
- Manual defrost for optimum control

All Models:

- Four casters, front two are lockable
- 1" (2.5cm) insulated access port
- Adjustable, epoxy-coated wire shelves are standard (optional drawers)
- TempTest electronic probe/alarm test
- Keyed on/off switch with setpoint security
- Self-closing door with 90° stop
- Built-in remote alarm contacts
- Optional 4-20 milliamp output

Thermo Scientific Revco High-Performance Freezers with Automatic Defrost

Temperature Range: -30°C (auto defrost)

Model No.	Cu.Ft. (L)	Voltage (Hz)	Certification	Amps/ Breaker (Plug)	Cabinet	Door	Adjustable Shelves	Int. Dimensions* H x D x W inches (mm)	Ext. Dimensions* H x D x W inches (mm)	Ship Weight lb (kg)
ULT430A ULT430D ULT430V ULT430W	4.9 (133)	115 (60) 208/230 (60) 230 (50) 230 (50)	UL UL CE CE	8.0/15 (P1) 6.0/15 (P4) 6.0/15 (P7) 6.0/15 (P8)	undercounter	single	3	20.0 x 20.5 x 20.0 (508 x 521 x 508)	33.4 x 26.0 x 24.0 (850 x 660 x 610)	220 (100)
Exterior height before caster installation.										
ULT1230A ULT1230V ULT1230W	11.5 (326)	115 (60) 230 (50) 230 (50)	UL UL CE	8.0/15 (P1) 8.0/15 (P7) 8.0/15 (P8)	space saver	single	4	52.4 x 21.0 x 20.0 (1331 x 553 x 508)	73.6 x 30.0 x 24.0 (1869 x 748 x 610)	280 (127)
ULT2330A ULT2330D ULT2330V ULT2330W	23.3 (659)	115 (60) 208/230 (60) 230 (50) 230 (50)	UL UL CE CE	16.0/20 (P1) 12.0/15 (P4) 12.0/15 (P7) 12.0/15 (P8)	upright	single	4	58.0 x 29.0 x 24.0 (1473 x 737 x 610)	79.2 x 37.2 x 28.0 (2012 x 945 x 711)	425 (193)
ULT3030A ULT3030D ULT3030V ULT3030W	29.2 (826)	115 (60) 208/230 (60) 230 (50) 230 (50)	UL UL CE CE	16.0/20 (P1) 12.0/15 (P4) 12.0/15 (P7) 12.0/15 (P8)	upright	single	4	58.0 x 29.0 x 30.0 (1473 x 737 x 762)	79.2 x 37.2 x 34.0 (2012 x 945 x 864)	445 (197)
ULT5030A ULT5030D ULT5030V ULT5030W	51.1 (1447)	115 (60) 208/230 (60) 230 (50) 230 (50)	UL UL CE CE	16.0/20 (P2) 12.0/15 (P4) 12.0/15 (P7) 12.0/15 (P8)	upright	double	8	58.0 x 29.0 x 52.5 (1473 x 737 x 1334)	79.2 x 37.2 x 56.5 (2012 x 945 x 1435)	600 (272)

* Published interior volumes are nominal; useable cu.ft. (L) capacities may be offset by shelves, drawers, blower coils, or cabinet protrusions. For specific cabinet dimensions and allowances, or for verification of clearance tolerances, contact our sales representative. Product performance may be affected by ambient temperature conditions, humidity conditions, sample loading preferences, and frequency of door openings. Contact our sales representative for specific inquiries regarding your application. 4.7 cu. ft. exterior dimensions are without casters.

► See pages 22-25 for Options and Accessories



Thermo Scientific Revco High-Performance Freezers with Manual Defrost

Temperature Range: -20°C (manual defrost)

Model No.	Cu.Ft. (L)	Voltage (Hz)	Certification	Amps/ Breaker (Plug)	Cabinet	Door	Adjustable Shelves	Int. Dimensions* H x D x W inches (mm)	Ext. Dimensions* H x D x W inches (mm)	Ship Weight lb (kg)
UGL2320A	23.3	115 (60)	UL	13.5/20 (P2)	upright	single, solid	4	58.0 x 29.0 x 24.0	79.2 x 37.2 x 28.0	425
UGL2320D	(659)	208/230 (60)	UL	5.6/15 (P4)				(1473 x 737 x 610)	(2012 x 945 x 711)	(193)
UGL2320V		230 (50)	CE	5.6/15 (P7)						
UGL2320W		230 (50)	CE	5.6/15 (P8)						
UGL3020A	29.2	115 (60)	UL	16.0/20 (P1)	upright	single	4	58.0 x 29.0 x 30.0	79.2 x 37.2 x 34.0	445
UGL3020D	(826)	208/230 (60)	UL	12.0/15 (P4)				(1473 x 737 x 762)	(2012 x 945 x 864)	(197)
UGL3020V		230 (50)	CE	12.0/15 (P7)						
UGL3020W		230 (50)	CE	12.0/15 (P8)						

* Published interior volumes are nominal; useable cu.ft. (L) capacities may be offset by shelves, drawers, blower coils, or cabinet protrusions. For specific cabinet dimensions and allowances, or for verification of clearance tolerances, contact our sales representative. Product performance may be affected by ambient temperature conditions, humidity conditions, sample loading preferences, and frequency of door openings. Contact our sales representative for specific inquiries regarding your application.



Plasma Freezers

Our **pre-set Revco high-performance -30°C plasma freezers with automatic defrost** are designed to meet AABB and FDA standards for safety and performance in plasma storage. Sample security and protection are especially critical when storing plasma.

Our units feature setpoint security with master switch control, plus a clearly visible temperature display and audio/visual alarm systems to assure proper operating conditions.

Five different models are available to meet your particular storage volume and lab space requirements.

- Forced air circulation for uniform temperature and fast door opening recovery
- Smart defrost with temperature guided cycle
- Standard, stainless steel interior
- Built-in chart recorder (4.9 cu. ft. model freestanding)
- Four casters, front two are lockable
- 1" (2.5cm) insulated access port
- TempTest electronic probe/alarm test
- Keyed on/off switch with setpoint security
- Self-closing door with 90° stop
- Built-in remote alarm contacts
- Optional 4-20 milliamp output

Thermo Scientific Revco High-Performance Plasma Freezers with Automatic Defrost

Temperature Range: -30°C (auto defrost)

Model No.	Cu.Ft./L (Plasma Box Capacity)**	Voltage (Hz)	Certification	Amps/ Breaker (Plug)	Cabinet	Door	Drawers	Int. Dimensions* H x D x W inches (mm)	Ext. Dimensions* H x D x W inches (mm)	Ship Weight lb (kg)
UFP430A	4.9/133	115 (60)	UL	8.0/15 (P1)	undercounter	single	2	20.0 x 20.5 x 20.0	33.4 x 26.0 x 24.0	220
UFP430D	(78)	208/230 (60)	UL	6.0/15 (P4)				(508 x 521 x 508)	(850 x 660 x 610)	(100)
UFP430V		230 (50)	CE	6.0/15 (P7)				Exterior height before caster installation		
UFP430W		230 (50)	CE	6.0/15 (P8)						
UFP1230A	11.5/326	115 (60)	UL	8.0/15 (P1)	space	single	7	52.4 x 21.0 x 20.0	73.6 x 30.0 x 24.0	365
UFP1230V	(273)	230 (50)	CE	8.0/15 (P7)	saver			(1331 x 533 x 508)	(1869 x 762 x 610)	(166)
UFP1230W		230 (50)	CE	8.0/15 (P8)						
UFP2330A	23.3/659	115 (60)	UL	16.0/20 (P2)	upright	single	7	58.0 x 29.0 x 24.0	79.2 x 37.2 x 28.0	425
UFP2330D	(532)	208/230 (60)	UL	12.0/15 (P4)				(1473 x 737 x 610)	(2012 x 945 x 711)	(193)
UFP2330V		230 (50)	CE	12.0/15 (P7)						
UFP2330W		230 (50)	CE	12.0/15 (P8)						
UFP3030A	29.2/826	115 (60)	UL	16.0/20 (P2)	upright	single	7	58.0 x 29.0 x 30.0	79.2 x 37.2 x 34.0	580
UFP3030D	(665)	208/230 (60)	UL	12.0/15 (P4)				(1473 x 737 x 762)	(2012 x 945 x 864)	(263)
UFP3030V		230 (50)	CE	12.0/15 (P7)						
UFP3030W		230 (50)	CE	12.0/15 (P8)						
UFP5030A	51.1/1447	115 (60)	UL	16.0/20 (P2)	upright	double	14	58.0 x 29.0 x 52.5	79.2 x 37.2 x 56.5	600
UFP5030D	(1064)	208/230 (60)	UL	12.0/15 (P4)				(1473 x 737 x 1334)	(2012 x 945 x 1435)	(272)
UFP5030V		230 (50)	CE	12.0/15 (P7)						
UFP5030W		230 (50)	CE	12.0/15 (P8)						

* Published interior volumes are nominal; useable cu. ft. (L) capacities may be offset by shelves, drawers, blower coils, or cabinet protrusions. For specific cabinet dimensions and allowances, or for verification of clearance tolerances, contact our sales representative. Product performance may be affected by ambient temperature conditions, humidity conditions, sample loading preferences, and frequency of door openings. Contact our sales representative for specific inquiries regarding your application. 4.7 cu. ft. exterior dimensions are without casters.

** Nominal capacity based on 250 mL plasma boxes.

Independent automated monitoring is required such as a chart recorder. Note: this medical application is considered Class II for FDA but is currently Class I for MDD.



Manual Defrost Enzyme Freezers

Our manual defrost **Revco high-performance, -20°C upright freezers** are designed for storage applications in which even slight intermittent coil warming during auto defrost cycles cannot be tolerated. Models feature gravity convection air systems for maximum temperature stability without blowers or fans.

- Cold wall convection cooling for temperature uniformity
- Manual defrost for optimum control
- Four casters, front two are lockable
- 1" (2.5cm) insulated access port
- Adjustable, epoxy-coated wire shelves are standard (optional drawers)
- TempTest electronic probe/alarm test
- Keyed on/off switch with setpoint security
- Self-closing door with 90° stop
- Built-in remote alarm contacts
- Optional 4-20 milliamp output



Optional, inkless, seven day, graphic, chart recorder

Control Panel:

Keyed on/off switch with set point security

Microprocessor control system with audio and visual alarms

Bright, digital temperature display

Easily accessible inventory system

Doors:

Spring-loaded, self closing doors with 90° stay-open feature

Lockable doors for added sample security

Smooth, ergonomic handle

► See pages 22-24 for Options and Accessories

Thermo Scientific Revco High-Performance Enzyme Freezers with Manual Defrost

Temperature Range: -20°C (manual defrost)

Model No.	Cu.Ft. (L)	Voltage (Hz)	Certification	Amps/ Breaker (Plug)	Cabinet	Door	Shelves	Int. Dimensions* H x D x W inches (mm)	Ext. Dimensions* H x D x W inches (mm)	Ship Weight lb (kg)
UEN2320A	23.3	115 (60)	UL	13.5/20 (P1)	upright	single	9	58.0 x 29.0 x 24.0	79.2 x 37.2 x 28.0	425
UEN2320D	(659)	208/230 (60)	UL	5.6/15 (P4)				(1473 x 737 x 610)	(2012 x 945 x 711)	(193)
UEN2320V		230 (50)	CE	5.6/15 (P7)						
UEN2320W		230 (50)	CE	5.6/15 (P8)						
UEN3020A	29.2	115 (60)	UL	16.0/20 (P1)	upright	single	9	58.0 x 29.0 x 30.0	79.2 x 37.2 x 34.0	445
UEN3020D	(826)	208/230 (60)	UL	12.0/15 (P4)				(1473 x 737 x 762)	(2012 x 945 x 864)	(197)
UEN3020V		230 (50)	CE	12.0/15 (P7)						
UEN3020W		230 (50)	CE	12.0/15 (P8)						

* Published interior volumes are nominal; useable cu.ft. (L) capacities may be offset by shelves, drawers, blower coils, or cabinet protrusions. For specific cabinet dimensions and allowances, or for verification of clearance tolerances, contact our sales representative. Product performance may be affected by ambient temperature conditions, humidity conditions, sample loading preferences, and frequency of door openings. Contact our sales representative for specific inquiries regarding your application.

Services

Electrical Information

Thermo Scientific Revco high-performance refrigerators and freezers are designed to meet UL and CE criteria for safety and performance. See ordering charts for certifications per specific voltages. All connections must comply with local electrical codes.

- Selection charts for each standard model list voltage, rated amperage, recommended circuit breaker size, and NEMA (National Electrical Manufacturers' Association, USA) electrical plug information
- Most refrigerators and freezers are supplied with line cord plugs, which require corresponding receptacles illustrated on the line cord plug reference chart to the right
- Site preparation requires availability of the proper receptacle; a dedicated circuit is required
- Special voltage selections may be available at extra cost and must be specified when ordering
- For questions regarding site preparation, installation and electrical connection, contact your sales representative

Certification of Calibration

Control, alarm and temperature recording systems are systematically calibrated at the factory for accurate performance. An optional Certificate of Calibration to an NIST (National Institute of Standards and Technology, formerly National Bureau of Standards) traceable instrument includes a Model Number and Serial Number Certificate (single point calibration). Multiple point calibration is also available. Calibration certificates must be requested when ordering; for details contact your sales representative.

Validation Testing Program

Validation testing services in advance of shipment can accelerate in-house FDA Installation Qualification (IQ) and Operation Qualification (OQ) programs. Validation services include documentation and performance reports, compressor and subsystem component specifications, microprocessor flow diagrams, software specifications and more. For more details, contact your sales representative.














Ordering Information

Your sales representative will assist you with choosing the correct refrigerator or freezer for your application.

- Each model number is voltage specific. For clarity, please include the voltage of your selected refrigerator or freezer when ordering
- When ordering your refrigerator or freezer, please consider current or future accessory requirements such as temperature recorders, extra shelves and alarm/monitoring systems
- Many accessories on the following pages are factory installed and must be specified when ordering

Standard Plug Option Configurations

Choose one of our specialty plugs to configure your freezer to meet local requirements

Model No.	Plug Description	Male End
Standard Plugs		
US125V20A	NEMA 5-20	
US230V15A	NEMA 6-15	
EU230V16A	Continental EU	
Specialty Plugs		
IT230V16A	Italy	
UK230V13A	Great Britain	
IN230V16A	India	
IS230V16A	Israel	
AU230V16A	Australia	
CH230V16A	China	
DK230V16A	Denmark	
AR230V16A	Argentina	
SW230V16A	Switzerland	
BR230V16A	Brazil	

Refrigerators and freezers supplied with line cord plugs (P) require corresponding receptacles illustrated in the Line Cord Plug Reference. Catalog selection charts list each standard model with voltage, rated amperage, recommended circuit breaker size and NEMA electrical plug information.

Options & Accessories

Productive use of your refrigerator or freezer can be enhanced with options and accessories specifically designed to improve utility and convenience. Many accessories are factory installed and must be specified with your original order. Field installed accessories may require the services of a factory authorized technician.

Note that some options and accessories may affect refrigerator or freezer performance; for more information contact your sales representative.



Shelves

Voltages and Serial Numbers

Serial number tags on all of our Revco units provide model numbers and voltage information needed for accurate selection of accessories ordered for field installation.

It is recommended that accessories be ordered when your refrigerator or freezer is ordered. Factory-installed accessories allow proper set-up without power-down or emptying the cabinet.

Glass Doors

Solid doors are standard on most refrigerators unless otherwise specified. Dual-pane glass doors are optional and must be specified when ordering. Contact your sales representative for information on heated glass doors.

Shelves

Additional epoxy-coated, open-wire shelves are designed to fit individual cabinets; shelves are available in full- and half-sizes. Undercounter models use full-size only.

Rollout Drawers

Optional stainless steel drawers, offered as an alternative to standard open wire shelving are adjustable with full extension. Drawers are factory installed and must be specified when ordering cabinet.





Rollout Doors



Enzyme Storage Bins



Alarm Delay Module

Temperature Chart Recorders

Optional 6" (152 mm) chart, 7-day temperature recorders use pressure sensitive chart paper; one box of 50 charts included. Built-in recorders must be specified when ordering. Recorders are standard on all blood bank refrigerators and plasma freezers.

Enzyme Storage Bin

Bins are supplied standard on our enzyme freezers. Additional bins are useful for storage and inventory management. Formed of high impact ABS plastic, off-white. Labels not included.

Digital Temperature Monitor

Simple, accurate and cost-effective, the digital temperature and power monitor provides both alarm/monitoring and digital temperature display in a single, self-contained unit. Standard features include high alarm, alarm mute and chirp, audio delay timer, remote alarm contacts (SPDT), NiCad battery backup, and low voltage AC power supply, 120V, AC.

- The monitor can be installed on or adjacent to any refrigerator or freezer
- Activates an audible and visual warning in case of power failure or overtemperature condition
- Choose from single probe digital models or multiple probe, microprocessor-based models
- Temperature range is -100°C to +25°C
- Probe size 1.25"L x 0.25" diameter (32 mm x 6 mm)

Alarm Delay Module

The alarm delay eliminates nuisance alarms due to intermittent or transitory conditions such as lightning or brief power outages. The adjustable delay requires an alarm condition to exist continuously for a pre-determined time (adjustable) before a signal is released to a central alarm/monitoring system or telephone dialer.

- Adjustable delay from 0.5 to 32 minutes
- Red alarm indicator light remains flashing after transient condition is corrected; requires manual reset
- Signals chronic alarm conditions which may indicate impending component failure; allows time for inspection or corrective maintenance
- Inserts variable time interval between detection of alarm condition and transmission of signal
- Includes accurate digital timing circuit adjustable from 0.5, 1, 2, 4, 8, 18, or 32 minutes
- Operates independent of line power; built-in battery and alarm test function uses customer supplied 9V battery

-20°C Laptop Cooler

- Protects enzymes, cells, reagents and solutions by maintaining freezer temperatures while on the laboratory bench ($T^{\circ} < 20^{\circ}\text{C}$ maintained up to 1 hour)
- Maintains freezer temperature during the frost free cycle, power failure and accidental door opening
- Printed grid on one way keyed lid for proper orientation and sample identification
- Molded of impact resistant polycarbonate; stackable, with locking handle

Options & Accessories Ordering Guide

Laboratory Refrigerators

		4.9 cu. ft. (133 L)	11.5 cu. ft. (326 L)	23.3 cu. ft. (659 L)	29.2 cu. ft. (826 L)	45.8 cu. ft. (1297 L)	51.1 cu. ft. (1447 L)	78.8 cu. ft. (2231 L)
		MODEL NO.	MODEL NO.	MODEL NO.	MODEL NO.	MODEL NO.	MODEL NO.	MODEL NO.
Shelves								
Epoxy-coated, full size		7125	7125	6696	6695	6696	6696	6696
Epoxy-coated, half size		n/a	n/a	6698	6697	6698	6698	6698
Door Options and Accessories								
LH swing, solid		7119	6995	6997	6999	n/a	n/a	n/a
LH swing, glass		n/a	6996	6998	7000	n/a	n/a	n/a
LH swing, heated glass		n/a	7073	7075	7087	n/a	n/a	n/a
RH swing, glass		7118	7066	7012	7013	n/a	n/a	n/a
RH swing, heated glass		n/a	7074	7086	7088	n/a	n/a	n/a
LH/LH swing, solid		n/a	n/a	n/a	n/a	n/a	7001	n/a
LH/LH swing, glass		n/a	n/a	n/a	n/a	n/a	7067	n/a
LH/LH swing, heated glass		n/a	n/a	n/a	n/a	n/a	7089	n/a
RH/RH swing, solid		n/a	n/a	n/a	n/a	n/a	7068	n/a
RH/RH swing, glass		n/a	n/a	n/a	n/a	n/a	7069	n/a
RH/RH swing, heated glass		n/a	n/a	n/a	n/a	n/a	7090	n/a
LH/RH swing, glass		n/a	n/a	n/a	n/a	n/a	7014	n/a
LH/RH swing, heated glass		n/a	n/a	n/a	n/a	n/a	7091	n/a
LH/RH swing, solid		n/a	n/a	n/a	n/a	n/a	7019	n/a
Roll-Out Drawers								
Complete Set	Cat. No. (qty)	7129 (2)	7445 (5)	6699 (6)	6704 (6)	n/a	6700 (12)	6701 (18)
(Single Drawers)		7122	7122	6702	6725	n/a	6702	6702
Drawers Dividers								
For blood bank refrigerators	Cat. No. (qty)	7027 (4)	7027 (4)	6206 (4)	6963 (5)	n/a	6206 (4)	6206 (4)
Casters (2" casters standard)								
3" casters (76 mm), set of 4*		6041-1	6041-1	6041-1	6041-1	6694	6041-1	6041-1
Finishes (adds 1" or 25 mm to unit height)								
Stainless steel interior (Not available on -20°C units)		7116	6199-3A	6115	6709	6711	6116	6117
Temperature Chart Recorders								
(Standard on blood bank units)								
Built-in, factory installed		n/a	6183-7	6183-7	6183-7	6183-7	6183-7	6183-7
Free-standing, customer installed		6199-3	6199-3	6199-3	6199-3	6199-3	6199-3	6199-3
Replacement chart paper, -40 to +25 box of 50		6184	6184	6184	6184	6184	6184	6184
Surge Suppressor								
Specify voltage with order		6402	6402	6402	6402	6402	6402	6402
Deluxe Electronic Remote Alarm								
Requires dedicated phone line		6224TA	6224TA	6224TA	6224TA	6224TA	6224TA	6224TA
Remote Alarm Module								
Specify voltage with order		5612-1A	5612-1A	5612-1A	5612-1A	5612-1A	5612-1A	5612-1A
Alarm Delay Module								
Specify voltage with order		6903	6903	6903	6903	6903	6903	6903
Digital Temperature Monitor (Specify voltage with order)								
-50°C to +50°C		6899	6899	6899	6899	6899	6899	6899
-100°C to +100°C		6900	6900	6900	6900	6900	6900	6900
-100°C to +125°C		6902	6902	6902	6902	6902	6902	6902
4-20 Milliamp Transmitter								
Factory installed		6907-1	6907-1	6907-1	6907-1	6907-1	6907-1	6907-1
Customer Installed		6907-2	6907-2	6907-2	6907-2	6907-2	6907-2	6907-2
+5°C Setpoint								
(Not Available for Blood Bank, Pharmacy or Chromatography Units)		7508TA	7508TA	7508TA	7508TA	n/a	7508TA	n/a
Seismic Restraint Kits								
Seismic restraint kit (basic)		N/A	TFR210	TFR210	TFR210	TFR210	TFR210	TFR210
Seismic restraint kit for OSHPD		N/A	TF-LRF12	TF-LRF23	TF-LRF30	TF-LRF45	TF-LRF50	7TF-LRF75

Options & Accessories Ordering Guide

Laboratory Freezers

	4.9 cu. ft. (133 L)	11.5 cu. ft. (326 L)	23.3 cu. ft. (659 L)	29.2 cu. ft. (826 L)	51.1 cu. ft. (1447 L)
	CAT. NO.	CAT. NO.	CAT. NO.	CAT. NO.	CAT. NO.
Shelves					
Epoxy-coated, full size	7125	7125	6696	6695	6696
Epoxy-coated, half size	n/a	n/a	6698	6697	6698
Door Options and Accessories					
LH swing, solid	7119	6995	6997	6999	n/a
LH/LH swing, solid	n/a	n/a	n/a	n/a	7001
RH/RH swing, solid	n/a	n/a	n/a	n/a	7068
LH/Rh swing, solid	n/a	n/a	n/a	n/a	7019
Roll-Out Drawers					
Freezer Complete Set	Cat. No. (qty)	7129 (2)	7446 (7)	6699 (7)	6704 (7)
(Single Drawers)		7122	7122	6702	6725
Drawers Dividers					
For plasma freezers	Cat. No. (qty)	7027 (4)	7027 (4)	6206 (4)	6963 (5)
Casters (2" casters standard)					
3" casters (76 mm), set of 4*		6041-1	6041-1	6041-1	6041-1
Finishes (adds 1" or 25 mm to unit height)					
Stainless steel interior (Not available on -20°C units)		7116	6199-3A	6115	6709
Temperature Chart Recorders (Standard on plasma units)					
Built-in, factory installed		n/a	6183-7	6183-7	6183-7
Free-standing, customer installed		6383-7	6383-7	6383-7	6383-7
Replacement chart paper, -40° to +25° box of 50		6184	6184	6184	6184
Surge Suppressor					
Specify voltage with order		6402	6402	6402	6402
Thermo Scientific Lab Cooler Modules					
Lab Cooler II (holds 24 1.5 mL tubes and 8 0.5 mL tubes)		6744	6744	6744	6744
Deluxe Electronic Remote Alarm					
Requires dedicated phone line		6224TA	6224TA	6224TA	6224TA
Remote Alarm Module					
Specify voltage with order		5612-1A	5612-1A	5612-1A	5612-1A
Alarm Delay Module					
Specify voltage with order		6903	6903	6903	6903
Digital Temperature Monitor (Specify voltage with order)					
-100°C to +25°C		6899	6899	6899	6899
Enzyme Storage Bin					
Labels not included		n/a	n/a	6736	n/a
4-20 Milliamp Transmitter					
For freezer		4706	4706	4706	4706
Seismic Restraint Kits					
Seismic restraint kit (basic)		N/A	TFR210	TFR210	TFR210
Seismic restraint kit for OSHPD		N/A	TF-LRF12	TF-LRF23	TF-LRF30

2" casters are pre-installed on all units, except 4.9 cu. ft. where casters are shipped uninstalled.

Media, Reagents and Consumables

Thermo Scientific™ Chromatography Columns and Consumables



Our outstanding product portfolio and experience will guide you through any chromatography challenge. Everything you need, all in one place. For predictable results separation after separation:

- Sample handling
- Sample preparation
- Reagents and standards
- GC columns and accessories
- HPLC and LC/MS columns and accessories

For additional information regarding these products, visit www.thermoscientific.com/chromatography



Thermo Scientific™ Nalgene™ and Nunc™ Lab Storage

Rely on Thermo Scientific Nalgene and Nunc products to safely store precious specimens, organize freezer space, and simplify sample retrieval.

For additional information visit,
www.thermoscientific.com/labwareandsupplies



Thermo Scientific™ Nalgene™ Mr. Frosty™ 5100 Cryo 1°C Freezing Container

Delivers low-cost cell cryopreservation and recovery, and features:

- Polycarbonate construction
- Blue high-density polyethylene closure
- White high-density polyethylene vial holder
- Foam insert

Mr. Frosty offer the critical, repeatable -1°C/ minute cooling rate required for successful cell cryopreservation and recovery. Requires only 100% isopropyl alcohol and -70°C mechanical freezer. It is labeled with graphic, step-by-step instructions and holds up to 18 vials. The holder is designed to prevent vials from contacting alcohol so there's no contamination by wicking; no removal of labels or printing on vials. Containers with alcohol can be stored at room temperature, saving valuable freezer space.



Thermo Scientific™ siRNA Research Products

Thermo Scientific™ Dharmacon™ pre-designed genome-wide siRNA products are the most trusted and most comprehensive offering available for your experimental needs.

- **ON-TARGET™ plus™ siRNA reagents** reduce off-target effects that may lead to toxicity or false phenotypes.
- **siGENOME™ siRNA reagents** have a proven track record of highly efficient target silencing from expert SMARTselection siRNA design.
- **Accell™ siRNA reagents** reagents are specially modified for delivery into difficult-to-transfect cells without a transfection reagent.
- **siRNA libraries** are pre-defined, custom and available on our Accell, ON-TARGET plus, and siGENOME technologies for human and mouse. Find a collection that's right for your, or submit a gene list of your own.
- **siRNA control reagents** include both product line based and specialty controls that ensure experimental reproducibility across multiple experimental applications.

For more information about these products, visit www.thermoscientific.com/dharmacon

Thermo Scientific Smart-Vue

with so much at stake,
obsessive is smart

The Thermo Scientific™ Smart-Vue™ wireless monitoring solution safeguards the integrity of precious samples by continuously monitoring critical parameters of laboratory equipment and securely logging data to give you peace-of-mind. This wireless solution features audit trail traceability to assist with conformance to 21 CFR part 11, and other regulatory requirements.



Smart

Continuous, real-time monitoring of critical parameters – alerting you remotely when sample integrity is threatened

Scalable

Flexibility to grow with your expanding laboratory needs

Simple

Easy to install, use and maintain

**For more information, contact
your sales representative.
Smart-Vue is not available in all
Radio Frequency (RF) regions.**

Note: Smart-Vue wireless monitoring kits are designed for first time users monitoring critical temperature parameters in ultra-low temperature freezers. Smart-Vue modules and sensors are available for temperature, RH, CO₂ concentration, differential pressure, 4-20mA output, ambient conditions and alarm/relay dry contacts. Solutions vary by RF regions worldwide and are compatible with multiple types of laboratory equipment. Please ask your sales representative to evaluate a Smart-Vue wireless monitoring solution that best meets your specific needs.





thermoscientific.com/cold

© 2013 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.

Australia +61 39757 4300
Austria +43 1 801 40 0
Belgium +32 53 73 42 41
China +800 810 5118 or
+400 650 5118
France +33 2 2803 2180
Germany national toll free 0800 1 536 376
Germany international +49 6184 90 6000

India toll free 1800 22 8374
India +91 22 6716 2200
Italy +32 02 95059 552
Japan +81 3 5826 1616
Netherlands +31 76 579 55 55
New Zealand +64 9 980 6700
Nordic/Baltic/CIS countries
+358 9 329 10200

Russia +7 812 703 42 15
Spain/Portugal +34 93 223 09 18
Switzerland +41 44 454 12 22
UK/Ireland +44 870 609 9203
USA/Canada +1 866 984 3766
Other Asian countries +852 2885 4613
Countries not listed +49 6184 90 6000

Thermo
SCIENTIFIC
Part of Thermo Fisher Scientific